



DA Series

Cold Water Pressure Washers

#1 in North America for High-Pressure Cleaning Equipment

Gasoline / Direct Drive



The reliable **Hotsy Triplex pump** has a one-piece forged brass manifold head and carries a 7-year limited warranty....best in the industry!

Five **quick-couple nozzles** made of hardened stainless steel and color coded for easy spray pattern selection: 0°, 15°, 25°, 40° nozzles plus a detergent nozzle

Hose and gun hanger keeps spray wand and hose safely stored

50 ft. wire-braided hose includes guards, couplers and one swivel end

Rugged **all-welded chassis** protected with all-weather, epoxy powder coat finish

Two **rubber pad feet** absorb vibration and keep machine from "walking"

Reliable **Honda GC or GX** gasoline engines with 3-year warranty* are CARB certified

High-pressure relief valve protects the machine and user

Model DA-383539

Downstream detergent injection allows remote detergent injection

Tubed pneumatic tires for easy handling

Thermal pump protector prevents excessive heat or pressure buildup for safety

Professional-duty high pressure **Trigger gun and wand**

EZ-start valve on 13 HP model for resistance-free pull starting

* Honda GC engine carries a 90-day commercial-use warranty or 2-year residential duty warranty

FEATURES

- 2.3 to 3.8 GPM / 2300 to 4000 PSI
- Honda GC & GX Gasoline engines
- Compact, lightweight design
- Hotsy 7-yr pump warranty

www.Hotsy.com

Nothing Cleans Like a Hotsy!

DA SERIES Cold Water GASOLINE Models

■ Honda GC & GX gasoline engines ■ 2.3 - 3.8 GPM @ 2300 to 4000 PSI ■ Compact / lightweight design ■ 7-yr Hotsy pump warranty

The Hotsy DA Series: The Right Choice for Professional Cleaning

SPECIFICATIONS

MODEL	GPM	PSI	ENGINE / MODEL	CC's	START	PUMP MODEL	DRIVE	HOSE	SHIP WT (lbs)
DA-232336	2.3	2300	Honda GC160	160	RECOIL	Comet BXD	Direct	25'	73
DA-232337	2.3	2300	Honda GC160	160	RECOIL	Legacy Axial	Direct	25'	72
DA-252739	2.5	2700	Honda GX200	196	RECOIL	HG2530G.1.1	Direct	50'	99
DA-354039	3.5	4000	Honda GX390	390	RECOIL	HS3540G.3	Direct	50'	157
DA-383539	3.8	3500	Honda GX390	390	RECOIL	HS4040G.2	Direct	50'	157

DIRECT DRIVE

Dimensions: 160 & 196 CC Machines 23"L X 22"W X 25"H; 390 CC Machines: 36.5"L X 23.5"W X 30.5"H



Clean better with Hotsy detergents

Hotsy pressure washers and parts washers clean best when matched with

specialty formulated Hotsy detergents. More than 40 liquids and powders meet every cleaning need imaginable. Nearly all contain Hotsy's exclusive advanced-formula HCC additives to help prevent scale build-up and to fight corrosion in your equipment. Most Hotsy detergents are USDA and Canadian Agriculture approved. All are highly concentrated, so a little goes a long way.

Looking to save time and money? See a Hotsy foamer in action!



Hotsy Accessories customize your application for top performance



100' E-Zee Hose Reel Kit



High-pressure turbo nozzles for faster cleaning

Telescoping wands extend to 24' to reach high places without scaffolding



High-pressure hoses from 30 to 150-ft. lengths



Rotary surface cleaner attaches to your pressure washer; reduces overspray and zebra striping

Spend some time with a Hotsy Expert

Hotsy has more than 160 local distributors in North America, all factory-trained to properly evaluate your high-pressure cleaning needs.

Over 80% of Hotsy's distributors have been supporting Hotsy systems for more than 20 years.



Rely on our network of seasoned service professionals for the safest, most effective and most efficient solution to your specific cleaning need.

Distributed by:



Tel: (800) 525-1976 Fax: (888) 880-9631
 www.Hotsy.com email: info@Hotsy.com
 P/N 9.800-477.0 Effective 8/13 Specifications & product descriptions subject to change without notice. ©2013 Hotsy
 A member of KÄRCHER North America

NOTE: We are constantly improving and updating our products. Consequently, pictures, features & specifications in this brochure may differ slightly from current models. Flow rates & pressure ratings may vary due to variances allowed by manufacturers of our machine components. We attempt to keep our machine performance within ± 5% of listed specifications.