



# 900/1400 Series

## Hot-Water Pressure Washers

#1 in North America for High-Pressure Cleaning Equipment

### Electric / Belt Drive



**Upright, vertical coil** with 3/4-inch schedule 80 pipe is wrapped with a thick foil blanket insulation, delivering high efficiency and maintains constant temperature using Natural Gas or LP Gas

Industry-standard **flue outlet** for quick installation

**Pressure relief valve** protects the machine and user from thermal expansion

Improved **auto-tensioning** system maintains belt tension on the pump with a torsion bar for precise tension adjustment

**Triple banded belt** for more efficient power transmission

**Adjustable upstream detergent injection** ensures high-pressure sudsing for better cleaning



**Hotsy-designed Triplex pumps** carry a 7-year limited warranty

Same **footprint** as previous generation for easy upgradability

**Programmable Smart Control Automation** provides complete control over the machine's run time, auto start/stop and time delay shut down functionality.



**Locking lid** prevents accidental removal of both panels around the belt and pulley

Concealed but accessible **Thermostat** reduces random user adjustments

Prewired to accept field installations of **remote controls**

Sleek side and front removeable **panels** provide easy access to the entire washer for service & maintenance

**50-ft. length of high-pressure hose** for easy cleaning in a large working area



### FEATURES

- 4.0 - 5.0 GPM @ 2000 to 3000 PSI
- NG Fired or LP Fired
- 208V or 230V, 1PH; 208V, 230V, 460V or 575V, 3PH
- ETL-Certified to UL-1776 safety standards

**Float tank** helps maintain constant water pressure and flow while helping to prevent sediment from entering the machine's components

**Insulated Hotsy trigger gun and insulated wand** with ergonomic, adjustable side handle

[www.Hotsy.com](http://www.Hotsy.com)

*Nothing Cleans Like a Hotsy!*

# 900 / 1400 SERIES Hot-Water ELECTRIC Models

- NG-Fired or LP-Fired
- 4.0 to 5.0 GPM @ 2000 to 3000 PSI
- Hotsy Triplex Pump with 7-yr warranty
- ETL-Certified for safety

## Stationary pressure washers for heavy-duty cleaning.

### SPECIFICATIONS

### BELT DRIVE

MODEL	GPM	PSI	HP	MOTOR RPM	VOLT/PH	AMP	FUEL	BTU/HR	PUMP MODEL	HOSE	SHIP WT
921P	4.0	2300	6.2	3450	208/1	28	LP	364,835	HHC506R.2	50'	700
921N	4.0	2300	6.2	3450	208/1	28	NG	364,835	HHC506R.2	50'	700
926P	4.0	2000	5	1800	575/3	7	LP	364,835	HHC506R.2	50'	660
926N	4.0	2000	5	1800	575/3	7	NG	364,835	HHC506R.2	50'	660
942P	4.0	2000	5	1725	208/3	18	LP	360,997	HM4030R.3	50'	590
942N	4.0	2000	5	1725	208/3	18	NG	364,835	HM4030R.3	50'	655
943P	4.0	2000	5	1725	230/1	25	LP	360,997	HM4030R.3	50'	685
943N	4.0	2000	5	1725	230/1	25	NG	364,835	HM4030R.3	50'	685
944P	4.0	2000	5	1725	230/3	16	LP	360,997	HM4030R.3	50'	580
944N	4.0	2000	5	1725	230/3	16	NG	364,835	HM4030R.3	50'	680
945P	4.0	2000	5	1725	460/3	8	LP	360,997	HM4030R.3	50'	585
945N	4.0	2000	5	1725	460/3	8	NG	364,835	HM4030R.3	50'	585
1451P	4.0	3000	8.2	3450	208/1	42	LP	364,835	HHC506R.2	50'	730
1451N	4.0	3000	8.2	3450	208/1	42	NG	364,835	HHC506R.2	50'	730
1452P	4.0	3000	7.5	1725	208/3	24	LP	360,997	HM4030R.3	50'	625
1452N	4.0	3000	7.5	1725	208/3	24	NG	364,835	HM4030R.3	50'	625
1453P	4.0	3000	7.5	1725	230/1	34	LP	360,997	HM4030R.3	50'	735
1453N	4.0	3000	7.5	1725	230/1	34	NG	364,835	HM4030R.3	50'	735
1454P	4.0	3000	7.5	1725	230/3	24	LP	360,997	HM4030R.3	50'	625
1454N	4.0	3000	7.5	1725	230/3	24	NG	364,835	HM4030R.3	50'	700
1455P	4.0	3000	7.5	1725	460/3	12	LP	360,997	HM4030R.3	50'	630
1455N	4.0	3000	7.5	1725	460/3	12	NG	364,835	HM4030R.3	50'	780
1456P	4.0	3000	8.2	3450	575/3	10	LP	364,835	HHC506R.2	50'	621
1456N	4.0	3000	8.2	3450	575/3	10	NG	364,835	HHC506R.2	50'	621
1473P	5.0	3000	10	1725	230/1	42	LP	378,617	HM4035R.3	50'	735
1473N	5.0	3000	10	1725	230/1	42	NG	390,025	HM4035R.3	50'	735
1474P	5.0	3000	10	1770	230/3	29	LP	378,617	HM4035R.3	50'	740
1474N	5.0	3000	10	1770	230/3	29	NG	390,025	HM4035R.3	50'	740
1475P	5.0	3000	10	1725	208/3	32	LP	378,617	HM4030R.3	50'	740
1475N	5.0	3000	10	1725	208/3	32	NG	378,617	HM4030R.3	50'	740

Dimensions: 47.5"l x 21"w x 51"h (including connectors and flue outlet)

### OPTIONS for 900 / 1400 SERIES

- **Remote Controls:** Controls the start up, shut down and with the optional detergent kit, the application of soap with easy to use low voltage switches.
- **8" Gas-Fired Draft Diverter:** For natural draft burner operation prevents downward / upward air affecting burner efficiency
- **Wheel Kit:** Includes LP Bottle Rack & Clamp; platform cart enables stationary 900/1400 models to become mobile; 2 swivel casters, 2 rigid
- **Inlet Water Solenoid** Prohibits water flow to float tank during idle
- **Soap Solenoid** Use with remote station for on/off detergent control
- **Power Damper Kit:** Motorized damper seals chimney from heat escape and reverse cold air flow

### Hotsy Accessories customize your application for top performance



Hose reels can be mounted on the wall to keep hose neatly stored and shop areas safe



Heavy-duty high-pressure hoses in lengths up to 150-ft.

Distributed by:



Nothing Cleans Like a Hotsy!

Tel: (800) 525-1976 Fax: (888) 880-9631

www.Hotsy.com email: info@Hotsy.com

P/N 9.801-491.0 Effective 7/15 Specifications & product descriptions subject to change without notice. ©2015 Kärcher North America



NOTE: We are constantly improving and updating our products. Consequently, pictures, features & specifications in this brochure may differ slightly from current models. Flow rates & pressure ratings may vary due to variances allowed by manufacturers of our machine components. We attempt to keep our machine performance within ± 10% of listed specifications.