



# 900/1400 Series

## Hot-Water Pressure Washers

#1 in North America for High-Pressure Cleaning Equipment

U.S. Design Patent No. 740,501 S

Electric / Belt Drive



**Upright, vertical coil** with 1/2-inch schedule 80 pipe is wrapped with a thick foil blanket insulation, delivering high efficiency and maintains constant temperature using Natural Gas or LP Gas

Industry-standard **flue outlet** for quick installation

**Pressure relief valve** protects the machine and user from thermal expansion

Improved **auto-tensioning** system maintains belt tension on the pump with a torsion bar for precise tension adjustment

**Triple banded belt** for more efficient power transmission


**Adjustable upstream detergent injection** ensures high-pressure sudsing for better cleaning



**Hotsy-designed Triplex pumps** carry a 7-year limited warranty

Same **footprint** as previous generation for easy upgradability

**Programmable Smart Control Automation** provides complete control over the machine's run time, auto start/stop and time delay shut down functionality.



**Locking lid** prevents accidental removal of both panels around the belt and pulley

Concealed but accessible **Thermostat** reduces random user adjustments

Prewired to accept field installations of **remote controls**

Sleek side and front removable **panels** provide easy access to the entire washer for service & maintenance

**50-ft. length of high-pressure hose** for easy cleaning in a large working area



### FEATURES

- 4.0 - 5.0 GPM @ 2000 to 3000 PSI
- NG Fired or LP Fired
- 208V or 230V, 1PH; 208V, 230V, 460V or 575V, 3PH
- ETL-Certified to UL-1776 safety standards

**Float tank** helps maintain constant water pressure and flow while helping to prevent sediment from entering the machine's components

**Insulated Hotsy trigger gun and insulated wand** with ergonomic, adjustable side handle

[www.Hotsy.com](http://www.Hotsy.com)

Nothing Cleans Like a Hotsy!

# 900 / 1400 SERIES Hot-Water ELECTRIC Models

■ NG-Fired or LP-Fired ■ 4.0 to 5.0 GPM @ 2000 to 3000 PSI ■ Hotsy Triplex Pump with 7-yr warranty ■ ETL-Certified for safety

## Stationary pressure washers for heavy-duty cleaning.

SPECIFICATIONS											BELT DRIVE
MODEL	GPM	PSI	HP	MOTOR RPM	VOLT/PH	AMP	FUEL	BTU/HR	PUMP MODEL	HOSE	SHIP WT
921P	4.0	2300	6.2	3450	208/1	32	LP	364,835	HM4030R.3	50'	700
921N	4.0	2300	6.2	3450	208/1	32	NG	364,835	HM4030R.3	50'	700
926P	4.0	2000	5	1800	575/3	7	LP	364,835	HM4030R.3	50'	660
926N	4.0	2000	5	1800	575/3	7	NG	364,835	HM4030R.3	50'	660
942P	4.0	2000	5	1725	208/3	18	LP	360,997	HM4030R.3	50'	590
942N	4.0	2000	5	1725	208/3	18	NG	364,835	HM4030R.3	50'	655
943P	4.0	2000	5	1725	230/1	25	LP	360,997	HM4030R.3	50'	685
943N	4.0	2000	5	1725	230/1	25	NG	364,835	HM4030R.3	50'	685
944P	4.0	2000	5	1725	230/3	16	LP	360,997	HM4030R.3	50'	580
944N	4.0	2000	5	1725	230/3	16	NG	364,835	HM4030R.3	50'	680
945P	4.0	2000	5	1725	460/3	8	LP	360,997	HM4030R.3	50'	585
945N	4.0	2000	5	1725	460/3	8	NG	364,835	HM4030R.3	50'	585
1451P	3.5	3000	8.2	3450	208/1	39	LP	364,835	HM4030R.3	50'	730
1451N	3.5	3000	8.2	3450	208/1	39	NG	364,835	HM4030R.3	50'	730
1452P	3.5	3000	7.5	1725	208/3	24	LP	360,997	HM4030R.3	50'	625
1452N	3.5	3000	7.5	1725	208/3	24	NG	364,835	HM4030R.3	50'	625
1453P	3.5	3000	7.5	1725	230/1	34	LP	360,997	HM4030R.3	50'	735
1453N	3.5	3000	7.5	1725	230/1	34	NG	364,835	HM4030R.3	50'	735
1454P	3.5	3000	7.5	1725	230/3	24	LP	360,997	HM4030R.3	50'	625
1454N	3.5	3000	7.5	1725	230/3	24	NG	364,835	HM4030R.3	50'	700
1455P	3.5	3000	7.5	1725	460/3	12	LP	360,997	HM4030R.3	50'	630
1455N	3.5	3000	7.5	1725	460/3	12	NG	364,835	HM4030R.3	50'	780
1456P	3.5	3000	8.2	3450	575/3	10	LP	364,835	HM4030R.3	50'	621
1456N	3.5	3000	8.2	3450	575/3	10	NG	364,835	HM4030R.3	50'	621
1473P	5.0	3000	10	1725	230/1	42	LP	378,617	HM4035R.3	50'	735
1473N	5.0	3000	10	1725	230/1	42	NG	390,025	HM4035R.3	50'	735
1474P	5.0	3000	10	1770	230/3	29	LP	378,617	HM4035R.3	50'	740
1474N	5.0	3000	10	1770	230/3	29	NG	390,025	HM4035R.3	50'	740
1475P	5.0	3000	10	1725	208/3	34	LP	378,617	HM4030R.3	50'	740
1475N	5.0	3000	10	1725	208/3	34	NG	378,617	HM4030R.3	50'	740

Dimensions: 47.5"l x 21"w x 51"h (including connectors and flue outlet)

### OPTIONS FOR 900/1400 SERIES


- Remote Controls for start up, shut down
- 8" Gas-Fired Draft Diverter - for natural draft burner operation; prevents downward/upward air affecting burner efficiency
- Wheel Kit - includes LP bottle rack & clamp; platform cart enables mobility; 2 swivel casters, 2 rigid
- Inlet Water Solenoid - prohibits water flow to float tank during idle
- Soap Solenoid - use with remote station for on/off detergent control

### SERVICE & REPAIR

Hotsy has more than 175 local dealers in North America, all factory-trained to properly evaluate your high-pressure cleaning needs.

Hotsy has factory-trained service technicians who will provide on-site maintenance for your cleaning equipment. Our techs have most common replacement parts on their service truck, and will quickly have your washer running smoothly.

FIND OUT MORE ONLINE: [HOTSY.COM](http://HOTSY.COM)



Distributed by:



Tel: (800) 525-1976 Fax: (888) 880-9631  
 www.Hotsy.com email: info@Hotsy.com  
 P/N HOT\_900-1400 Effective 05/18



Specifications & product descriptions subject to change without notice.  
 Hotsy's manufacturing facilities have established and apply a quality and environmental management system to be ISO 9001:2008 and ISO 14001:2001 certified.  
 ©2018 Kärcher North America

NOTE: We are constantly improving and updating our products. Consequently, pictures, features & specifications in this brochure may differ slightly from current models. Flow rates & pressure ratings may vary due to variances allowed by manufacturers of our machine components. We meet the CETA testing specs for machine performance at ± 10% and in some cases are tighter within ± 5% of listed specifications.