



9400 Series

Hot-Water Heaters

North America's #1 Manufacturer of High-Quality Cleaning Equipment

- 6 to 10 GPM output; up to 3200 PSI
- Operates on 115V / 1PH
- Attaches to cold-water pressure washer to achieve benefits of hot water cleaning

Choose from 4 Models

Hotsy 9400 Series Heater Modules deliver the cleaning punch you need.

The **9400 Series heater modules** give customers the flexibility to "convert" a cold water pressure washer into a hot water unit. By attaching the heater module to a cold water pressure washer, the pressurized water is now heated to produce all the benefits of hot water cleaning. The four models use fuel oil, diesel or natural gas to heat the water using Hotsy's high-efficiency, vertical heating coil.

All models operate on 115V and are ETL safety certified. Gas-fired models feature electronic ignition. They are designed to attach to cold water pressure washers with cleaning power of 6 to 10 GPM and up to 3200 PSI. We recommend using the Hotsy 1700 Series stationary cold-water pressure washers.



Model 9452 (Natural Gas, 540,000 BTU/Hr.) shown with Model 1700 (sold separately) with optional hose reel, cart, caster wheel kit and stainless steel base & cover



Model 9462
Natural Gas,
920,000 BTU/Hr.

Fuel-burner types available:

- Diesel • Kerosene**
- Home Heating Oil**
- Natural Gas • LP Gas (optional)**



Fleet applications



Oilfield applications



Food processing applications

OPTIONS for 9400 SERIES

- **Natural Gas to LP Conversion for Model 9452** (Factory installed)
- **Natural Gas to LP Conversion for Model 9462** (Factory installed)



Heater coil carries a 5-year warranty



Hotsy-designed Triplex pumps carry a 7-year limited warranty

www.Hotsy.com

Nothing Cleans Like a Hotsy!

9400 SERIES Hot Water Heater Modules

■ Oil or Natural Gas Heaters ■ 115V / 1PH ■ 540,000 to 920,000 BTU/Hr. ■ Diesel, Kerosene, Home Heating Oil, Natural Gas or Propane fuels

Designed for tough, industrial cleaning.

SPECIFICATIONS


| Model | 9450 | 9452 | 9460 | 9462 |
|--|--|---|---|---|
| PSI (Max) | 3200 | 3200 | 3200 | 3200 |
| Temperature Range | 98° rise @ 10 GPM 164° rise @ 6 GPM | 76° rise @ 10 GPM 126° rise @ 6 GPM | 129° rise @ 10 GPM 215° rise @ 6 GPM | 129° rise @ 10 GPM 215° rise @ 6 GPM |
| Burner Fuel | #1 or #2 Diesel Fuel, Kerosene or #1 Home Heating Oil | Natural Gas | #1 or #2 Diesel Fuel, Kerosene or #1 Home Heating Oil | Natural Gas |
| Type | Pressure-atomizing, forced-air, automatic electric ignition, UL approved. | Ring-type with aspirating spuds, natural draft. | Pressure-atomizing, forced-air, automatic electric ignition, UL approved. | Ring-type with aspirating spuds, natural draft. |
| Input | 700,000 BTU/Hr. | 540,000 BTU/Hr. | 920,000 BTU/Hr. | 920,000 BTU/Hr. |
| Voltage | 115V / 1PH | 115V / 1PH | 115V / 1PH | 115V / 1PH |
| Controls | Safety shut-off primary controller | 24 V programmed ignition controls with intermittent automatic spark-ignited pilot and electronic safety flame monitoring. AGA approved. | Safety shut-off primary controller | 24 V programmed ignition controls with intermittent automatic spark-ignited pilot and electronic safety flame monitoring. AGA approved. |
| Thermal rupture disk; temperature control to adjust water; high-pressure flow switch for automatic burner shut-off protection. | | | | |
| Heating Coil | 3/4" Schedule 80, ASTM A53 close coiling pipe, resistance butt-welded into continuous length, 3200 PSI hydrostatic pressure tested, 28,000 PSI burst pressure rated, vertically fired. | | | |
| Stack Size | 10" OD. Gas-fired units require draft diverter | | 12" OD. Gas-fired units require draft diverter | |
| Materials & Finish | Angle-iron frame, heavy-gauge welded cabinet finished with high-gloss powder coat. | | | |
| Dimensions | 32.5" L x 25" W x 50.5" H | | 40.5" L x 32" W x 65" H | |
| Net Weight | 495 lbs | 470 lbs | 865 lbs | 880 lbs |
| Shipping Weight | 525 lbs | 500 lbs | 920 lbs | 935 lbs |

DON'T FORGET THE SOAP!

Hotsy pressure washers clean best when matched with specially formulated Hotsy detergents. Nearly all contain Hotsy's exclusive advanced-formula HCC additives to help prevent scale build-up and to fight corrosion in your equipment. All are highly concentrated, so a little goes a long way.

SERVICE & REPAIR

Hotsy has more than 175 local dealers in North America who are trained to properly evaluate your high-pressure cleaning needs. Our factory-trained service technicians provide on-site maintenance for your cleaning equipment and have most common replacement parts on their service trucks. They will quickly have your washer running smoothly.



PARTS & ACCESSORIES

Your local Hotsy dealer would be happy to provide an onsite demonstration to determine which pressure washer accessories will help speed cleaning and lower your costs. In addition, you'll find a number of accessories designed to speed cleaning, the most common accessories are telescoping wands, pivot and non-pivot hose reels, flat surface cleaners and high pressure turbo nozzles.



FIND OUT MORE ONLINE: HOTSY.COM



Distributed by:

hotsy® *Nothing Cleans Like a Hotsy!*

Tel: (800) 525-1976 Fax: (888) 880-9631
www.Hotsy.com email: info@Hotsy.com

P/N 8.914-244.0 / HOT_9400S Effective 10/17

Specifications & product descriptions subject to change without notice.

Hotsy's manufacturing facilities have established and apply a quality and environmental management system to be ISO 9001:2008 and ISO 14001:2001 certified.

A member of KÄRCHER North America

©2017 Hotsy

NOTE: We are constantly improving and updating our products. Consequently, pictures, features & specifications in this brochure may differ slightly from current models. Flow rates & pressure ratings may vary due to variances allowed by manufacturers of our machine components. We meet the CETA testing specs for machine performance at ±10% and in some cases are tighter within ±5% of listed specifications.