



DBA Series

Aluminum Frame Cold Water Pressure Washers

#1 in North America for High-Pressure Cleaning Equipment

Gasoline / Direct Drive



Weldless corrosion resistant **aluminum frame** with 1-1/4" handles for maximum durability

Easy to push and pull thanks to an innovative frame shape and ideal weight distribution

Handle also adjusts for height for **ergonomical operation**

Four quick-couple nozzles made of hardened stainless steel and color-coded for easy spray pattern selection: 0°, 15°, 25° & 40°

Reliable **Honda GX** commercial-duty gasoline engines with 3-year warranty and vibration isolation for smooth operation

Pump support bracket extends engine crankshaft service life

The commercial-duty **Crankcase pump** carries a 7-year limited warranty... best in the industry!

Thermal pump protector prevents excessive heat or pressure buildup for safety

Cast aluminum rotary joints allow **the handle to fold down** for storage and easy transport.

Hose and gun hangers keeps spray wand and hose safely stored

Professional-duty **Trigger gun and spray wand** with adjustable side grip

50 ft. steel-wire braided high-pressure hose includes 24-inch hose guard for burst protection and swivel crimp fitting for tangle-free handling. Rated for 4,000 PSI.

FEATURES

- 2.5 to 3.8 GPM / 2700 to 4000 PSI
- 196 to 389 CC Gasoline Engines
- Aluminum frames, lightweight design
- 7-yr pump warranty

10" 4-ply tubed pneumatic tires for easy maneuvering

Two **Rubber Pad Feet** absorb vibration and keep machine from "walking"

www.Hotsy.com

Nothing Cleans Like a Hotsy!

DBA SERIES Cold Water GASOLINE Models

■ 196 to 390 CC gasoline engines ■ 2.5 to 3.8 GPM @ 2700 to 4000 PSI ■ Compact / lightweight design ■ 7-yr Hotsy pump warranty

The Hotsy DBA Series: The Right Choice for Tough, Cold-Water Cleaning

SPECIFICATIONS

MODEL	GPM	PSI	CC's (HP)	ENGINE	START	PUMP MODEL	DRIVE	HOSE	DIMENSIONS	SHIP WT (lbs)
DBA-252739	2.5	2700	196 (6.5)	Honda GX200	RECOIL	HG2530G.1	DIRECT	50'	39.3"Lx22.5"Wx39.6"H	125
DBA-303039	3.0	3000	270 (9)	Honda GX270	RECOIL	HG3035G1.1	DIRECT	50'	39.3"Lx22.5"Wx39.6"H	148
DBA-354039	3.5	4000	390 (13)	Honda GX390	RECOIL	HS3540G.3	DIRECT	50'	41"Lx23"Wx40"H	167
DBA-383539	3.8	3500	390 (13)	Honda GX390	RECOIL	HS4040G.2	DIRECT	50'	40.8"Lx22.5"Wx39.6"H	172



Clean better with Hotsy detergents

Hotsy pressure washers and parts washers clean best when matched with specially formulated Hotsy detergents. More than 40 liquids and powders meet every cleaning need imaginable. Nearly all contain Hotsy's exclusive advanced-formula HCC additives to help prevent scale build-up and to fight corrosion in your equipment. Most Hotsy detergents are USDA and Canadian Agriculture approved. All are highly concentrated, so a little goes a long way.

Looking to save time and money? See a Hotsy foamer in action!



Spend some time with a Hotsy Expert

Hotsy has more than 160 local distributors in North America, all factory-trained to properly evaluate your high-pressure cleaning needs.

Over 80% of Hotsy's distributors have been supporting Hotsy systems for more than 20 years.

Rely on our network of seasoned service professionals for the safest, most effective and most efficient solution to your specific cleaning need.



OPTIONS

- Downstream Detergent Injector

Hotsy Accessories customize your application for top performance

Telescoping wands extend to 24' to reach high places without scaffolding

High-pressure turbo nozzles for faster cleaning



Heavy-duty, high-pressure hoses in lengths up to 150-ft.



Rotary surface cleaner attaches to your pressure washer; reduces overspray and zebra striping

Distributed by:



Tel: (800) 525-1976 Fax: (888) 880-9631
 www.Hotsy.com email: info@Hotsy.com
 P/N 9.801-314.0 Effective 8/13 Specifications & product descriptions subject to change without notice. ©2013 Hotsy
 A member of KÄRCHER North America



NOTE: We are constantly improving and updating our products. Consequently, pictures, features & specifications in this brochure may differ slightly from current models. Flow rates & pressure ratings may vary due to variances allowed by manufacturers of our machine components. We attempt to keep our machine performance within ± 5% of listed specifications.